



# CHINMORE INDUSTRY CO.,LTD

## Specification

1. Cable Assembly with RF Connector
2. *Chinmore's* No: CX-MMCX174SMA-240
3. Frequency: 1~3GHz
4. VSWR: 2.0:1
5. Cable: RG-174 200mm
6. Connector: SMA F(BH) & RA MMCX M

✧RoHS Compliant

✧ISO 9001 & ISO 14001

Cable	RG174/U	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> <b>ROHS</b>          ISO 9001          ISO 14001       </div>
OD	ø2.7±0.15mm	
Cover	Black	
MMCX M 90°	Gold (鍍金)	
SMA F(BH)	Gold (鍍金)	

  

Material:		Treatment:		竣茂工業有限公司 Chinmore Industry CO .LTD			
Drawer	Design	Aprov	Tolerance	Unit: mm		TITLE	MMCX M(90°)+174U+SMA F(BH)
				Ver: C	Scale 1:1	Model NO	
NO	DESCRIPTION	MATERIAL	FINISH	QTY	File NO: QR0402	Drawing NO	100-21010-0006
Part NO	CX-MMCX174SMA-240						

Frequency (MHz)	VSWR	Insertion Loss (dB)
1000	1.07	-0.37
2000	1.24	-0.65
3000	1.50	-0.97

## TEST Report

