



# CHINMORE INDUSTRY CO.,LTD

## Specification

1. Cable Assembly with RF Connector
2. *Chinmore's* No: CX-FME174MMCX-117
3. Frequency: 1~3GHz
4. VSWR: 2.0:1
5. Cable: RG-174 300mm
6. Connector: FME M Bulkhead & RA MMCX M

✧RoHS Compliant

✧ISO 9001 & ISO 14001

Cable	RG174/U	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> <b>ROHS</b>            ISO 9001            ISO 14001         </div>
OD	ø2.7±0.15mm	
Cover	Black	
MMCX 90° M	Gold(鍍金)	
FME(BH)M	NI(鍍鎳)	

  
  

Material:		Treatment:		竣茂工業有限公司 Chinmore Industry CO.,LTD			
Drawer	Design	Aprov	Tolerance	Unit:	mm	TITLE	MMCX 90° M+174U+FME(BH)M
			X=±0.5	Ver: A	Scale 1:1	Model NO	Drawing NO
			X=±0.2				
			XXX=±0.05				
NO	DESCRIPTION	MATERIAL	FINISH	Q'TY	File NO: QR0402		
Part NO	CX-FME174MMCX-1179				Drawing NO 100-23005-175		

Frequency (MHz)	VSWR	Insertion Loss (dB)
1000	1.58	-0.50
2000	1.85	-0.94
3000	1.76	-1.11

## TEST Report



