



CHINMORE INDUSTRY CO.,LTD

Specification

1. Cable Assembly with RF Connector
2. Chinmore's No: CX-MMCX316SMA-1107
3. Frequency: 1~3GHz
4. VSWR: 2.0:1
5. Cable: RG-316 200mm
6. Connector: RA MMCX M & SMA F Bulkhead Straight

✧RoHS Compliant

✧ISO 9001 & ISO 14001

Cable	RG316/U
OD	Ø2.53±0.1mm
Cover	Brown (棕)
MMCX M RA	Gold (鍍金)
SMA F(BH)H A型	Gold (鍍金)

ROHS
 ISO 9001
 ISO 14001

ORING

WASHER

NUT

Material:		Treatment:		竣茂工業有限公司 Chinmore Industry CO.,LTD			
Drawer	Design	Aprov	Tolerance	Unit:	mm	TITLE	MMCX M RA+316U+ SMA F(BH)H A型
機構 15.11.3 詹曉楠	工程 15.11.3 蔡文基	X=±0.5		Ver: A	Scale 1:1	Model NO	
		X=±0.2					
		X=±0.1					
		XXX=±0.05					
Part NO	CX-MMCX316SMA-1107	File NO	QR0402	Drawing NO	100-23005-0164		

Frequency (MHz)	VSWR	Insertion Loss (dB)
1000 MHz	1.26	-0.39
2000 MHz	1.51	-0.63
3000 MHz	1.65	-0.98

TEST Report



