



CHINMORE INDUSTRY CO.,LTD

Specification

1. Cable Assembly with RF Connector
2. *Chinmore's* No: CX-SMA316SMA-1677
3. Frequency: 600MHZ~3GHz
4. VSWR: 2.0:1
5. Cable: RG-316 300mm
6. Connector: RA SMA M & SMA F Bulkhead

✧RoHS Compliant

✧ISO 9001 & ISO 14001

Cable	RG316/U	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> ROHS ISO 9001 ISO 14001 </div>
OD	∅2.53±0.1mm	
Cover	Brown (棕)	
RA SMA M	Gold (鍍金)	
SMA F(BH)	Gold (鍍金)	

Material:	Treatment:	竣茂工業有限公司 Chinmore Industry CO.,LTD			
Drawer	Design	Aprov	Tolerance	Unit:	mm
			X=±0.1		
			X=±0.05	Ver:	A
			X=±0.02	Scale	1:1
Title		RA+SMA M+RG316+SMA F(BH)			
Model NO		WIREAC1757			
File NO		QR0402			
Drawing NO		100-23005-0257			

NO	DESCRIPTION	MATERIAL	QTY
Part NO	CX-SMA316SMA-1677		

Frequency (MHz)	VSWR	Insertion Loss (dB)
600 MHz	1.07	-0.31
900 MHz	1.05	-0.46
1575 MHz	1.17	-0.69
1800 MHz	1.19	-0.81
2000 MHz	1.22	-0.85
2100 MHz	1.20	-0.88
2400 MHz	1.33	-0.88
2700 MHz	1.48	-1.29
3000 MHz	1.56	-1.21

TEST Report

