



CHINMORE INDUSTRY CO.,LTD

Specification

1. Mini Coaxial Cable Assembly with RF Connector
2. *Chinmore's* No: CX-MHF113SMA-1148
3. Frequency: 600Mhz~3Ghz
4. VSWR: 2.0:1
5. Cable: Ø1.13 50mm
6. Connector: SMA F Bulkhead Straight

✘RoHS Compliant

✘ISO 9001 & ISO 14001

Cable	Ø1.13±0.02mm	 ISO 9001 ISO 14001
Cover	Light gret	
MHF(IPX)	Gold(鍍金)	
SMA (BH) F	Gold(鍍金)	

Material:		Treatment:		竣茂工業有限公司 Chinmore Industry CO .LTD			
Drawer	Design	Draw	Tolerance	Unit:		TITLE	MHF+1.13鍍料+SMA F(BH)
	89.1.13		X=±0.5 .X=±0.2 .XX=±0.1 .XXX=±0.05	mm			
Part NO	CX-MHF113SMA-1148			Ver: A	Scale 1:1	Model NO	
				File NO: QR0402	Drawing NO	100-23005-171	

Frequency (MHz)	VSWR	Insertion Loss (dB)
600 MHz	1.06	-0.48
1000 MHz	1.09	-0.64
1500 MHz	1.12	-0.78
1800 MHz	1.14	-0.89
2000 MHz	1.25	-0.97
2100 MHz	1.27	-0.97
2400 MHz	1.18	-1.08
2700 MHz	1.46	-1.21
3000 MHz	1.21	-1.21

Test Report



