



CHINMORE INDUSTRY CO.,LTD

Specification

1. Product Type: RF Cable Assembly
2. *Chinmore's* No: CX-SMA174SMA-1555
3. Frequency: 1~3 GHz
4. VSWR: 2.0:1
5. Cable: RG-174
6. Connector: SMA (M) & SMA F (BH)

✧RoHS Compliant

✧ISO 9001 & ISO 14001

Cable	RG174/U	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> ROHS ISO 9001 ISO 14001 </div>
OD	∅2.6±0.1mm	
Cover	Black	
SMA M	Gold(鍍金)	
SMA(BH)F	Gold(鍍金)	

SR : A-4002
MATERIAL : 40P

HEAT SHRINK TUBE

Dimensions: 7.80, 6.10, 10.5, 700±25, 14.80, 1/4"-36P, ∅10.2

Material:	Treatment:	竣茂工業有限公司 Chinmore Industry CO.,LTD	
Drawer: 陳俊帆	Design: 蔡文華	Approval: 蔡文華	Tolerance: X=±0.5, Y=±0.2, Z=±0.1, XXX=±0.05
Unit: mm	Ver: A	Scale: 1:1	TITLE: SMA M+174U+SMA(BH)F
Model NO: WIREAC1717	File NO: QR0402	Drawing NO: 100-23005-0251	

NO	DESCRIPTION	MATERIAL	QTY
Part NO	CX-SMA174SMA-1555		

Frequency (MHz)	VSWR	Insertion Loss (dB)
1000 MHz	1.15	-0.86
2000 MHz	1.11	-1.27
3000 MHz	1.32	-1.87

Test Report



